

METHOD AND APPARATUS FOR DELIVERING MATERIAL TO A DESIRED LOCATION

5 Inventors: Robert R. Karpman, Thomas M. Hansen, Anna G. U. Brantley

TECHNICAL FIELD

10 The present invention generally relates to a method and apparatus for delivering material to a desired location through use of a slotted delivery device and, more particularly, to a bone screw which is configured for delivery of an injectable material into a bone.

BACKGROUND

15 In a number of medical procedures it becomes necessary to deliver material to a desired location. For example, in connection with many cancer treatments, particularly treatments to bones inflicted with cancer cells, it is desirable to deliver materials, usually in injectable form, to particular locations within the bone. In other instances, particularly when use of bone screws is desirable, materials, also usually of an injectable form, often need to be delivered to aid in fixation of the screw.

20 In the context of the present invention, as will be discussed in greater detail hereinbelow, the present inventors have discovered methods and apparatus which offer advantages over currently known methods and apparatus useful in the administration of such materials. For convenience of explanation and illustration, the present invention will be described in conjunction with various applications, but principally, bone screw and drug or other medication delivery systems. It should be appreciated, however, that various other applications and
25 embodiments will be apparent in light of the following disclosure.

30 In the context of bone screws, as is known, bone screws may be attached to bones for any number of reasons, but generally such screws are attached for the purpose of repair of the weakened bone structure to support bones or bone structure which have become broken or weakened. In many cases, the break or weakening of the bone is in whole, or at least in part, due to disease. That is, the bone breaks or weakens as a result of disease, *e.g.*, osteoporosis. Current

techniques, in general, do not take into consideration that condition in the context of the repair. Stated another way, the technique used to repair bone often fails to address the situation under which the bone broke or weakened in the first place.

For example, in accordance with conventional methods of attaching bone screws to bones, bone cement (typically an acrylic resin material) is injected through a pilot hole drilled into the bone prior to inserting the bone screw. After the bone screw is inserted into the site, the bone cement theoretically hardens to strengthen the fixation site. This method, however, lacks control over the location or amount of bone cement applied. For example, it is often difficult to control the placement of adhesive near tissue regions, specifically in the spinal cord region, and improper placement can result in injury. Moreover, too little bone cement or improper placement of the bone cement may result in a weak fixation site, which may lead to undesirable extraction of the bone screw from the fixation site. For example, if the bone has been broken due to, in whole or in part, a medical condition, the use of cement in this fashion may not materially enhance fixation. Specifically, if the bone is weakened due to, for example, osteoporosis, then merely adding an adhesive to the area, particularly if applied in a weakened area, may not address the pre-existing condition.

Moreover, in some cases use of the adhesive in this conventional manner can result in even more deleterious effects. Consider, for example, the case in which the adhesive begins to cure before, or during the insertion of the screw. In such a case, instead of enhancing the fixation of the screw, the adhesive may actually bind to the distal end of the screw, and, as the screw is inserted, cause further damage to the already weakened bone. Such effects, of course, may not be immediately detectable. That is, in some cases, while an initial "fix" may be obtained, the overall weakening of the fixation site may result in a weakening of the attachment over time, or in the best of cases, simply not aid in securing long term fixation.

Various bone screw configurations are known. For example, cannulated screws are known and typically used for such conventional applications. Alternatively, such cannulated screws are also utilized in connection with various pressurizing techniques. In connection with these techniques, suction is used to suck (*i.e.*, withdraw) the blood and fat out of the bone canal. For example, in U.S. Patent No. 5,047,030 issued September 10, 1991 to Draevert, a suction

drainage bone screw is described. The screw described is used initially to withdraw the blood and fat from a region surrounding the screw, such as by use of suctioning. While described as an advantage over existing pressurizing techniques, in all of the disclosed embodiments the removal of material is an important, if not essential aspect of the screw's success.

5 As described in the '030 patent, the bone screw is used to suck blood, fat and bone marrow out of the bone canal and its vicinity for suction drainage in the application of bone cement. Specifically, as described in the '030 patent, a cannulated bone screw is anterolaterally inserted into a distal tip of the prosthesis into a cortico-spongious plug, to ensure that the distal and proximal medullary canal remain delimited from the screw by means of the filter. The bone
10 is then filled with bone cement, mixed under vacuum but pre-compressed prior to introduction to the bone, *i.e.*, femur. In accordance with the disclosed embodiment, the bone cement is sucked deep down into the femur by the vacuum applied via the distal cannulated bone screw. Once a prosthesis component is inserted, the distal vacuum lead is pinched off and the vacuum then proximately applied until the cement has hardened.

The '030 patent specifically teaches against the use of bone cement under the so-called bone lavage and high pressurizing technique due to the disclosed number of fatalities resulting from such use. The method disclosed in the '030 patent and the devices used are complex. There thus exists a long felt and unresolved need for a bone screw and method of use of the same which overcomes the disadvantages of the prior art.

20 Moreover, the screw of the '030 patent, in accordance with one of its preferred embodiments, includes a number of radially extending transverse canals denoted by the numeral 4 in the '030 patent. As described in the '030 patent, the bone screw preferably exhibits several transverse canals, preferably 2 to 9 and more preferably 4 to 6 which contact the longitudinal canal. These holes are disclosed as enabling further increase in the effect of the partial vacuum.
25 The use of numerous radially extending apertures, particularly in the fashion shown in the '030 patent, has the potential deleterious effect of reducing the integrity of the screw itself, *i.e.*, weakening the screw.

Various drug delivery devices are also known, for example in the '030 patent, the screws disclosed therein are described as also having drug delivery capabilities. Nevertheless, the drug

delivery capabilities are minimized by the potential lack of integrity of the screw itself and such screws do not offer advantages particularly for re-use which may be desirable in numerous cases.

Suffice it to say that numerous disadvantages exist with currently known methods and apparatus for delivery of material to a desired location. There is thus a long felt need to address these disadvantages through use of a device which is relatively easy to make and use.

SUMMARY OF THE INVENTION

The present invention provides a method and apparatus for the effective delivery of material to a desired location. In accordance with a preferred embodiment of the present invention, a device (*e.g.*, a bone screw) is provided which includes a head portion, a shaft portion, and a tip portion. The head portion further includes an injection site wherein an injection device, such as a syringe, or an attachment mechanism can be removably attached.

In accordance with yet other embodiments of the present invention, devices are disclosed which enable the effective and efficient delivery of material in a reliable manner to diseased sites, the devices being provided with enhanced integrity. In accordance with preferred aspects of this embodiment of the present invention, such devices are particularly configured for repeated use.

BRIEF DESCRIPTION OF THE DRAWING

The present invention will hereinafter be described in conjunction with the appended drawing figures wherein like numerals denote like elements, and

Figure 1 is a schematic cut-away view of an exemplary long bone;

Figure 2 is a cross-sectional view of a fracture formed in a bone;

Figure 3 is a cross-sectional view of an exemplary fracture site in a bone which has been prepared for insertion of a bone screw in accordance with the present invention;

Figure 4 is a cross-sectional view of a device in accordance with one embodiment of the present invention in the form of a bone screw which is inserted into the fracture site shown in Figure 3;

Figure 5 is a side view of a device in accordance with one embodiment of the present invention in the form of a bone screw;

Figure 5A is a cross-sectional view of the bone screw shown in Figure 5 taken through line 5-5;


5  Figure 5B is a top view of a device in accordance with one embodiment of the present invention, such as the top view of the bone screw of Figure 5;

Figure 6 is a cross-sectional view of a device in accordance with one embodiment of the present invention in the form of a bone screw useful in mending a fracture of an osteoporotic bone;

10 Figure 7 is a cross-sectional view of a device in accordance with one embodiment of the invention in the form of another bone screw provided with a plurality of delivery apertures;

Figure 8 is a side view of a device in accordance with one embodiment of the present invention in the form of yet another bone screw;

Figure 8A is a cross-sectional view of the bone screw of Figure 8;

Figure 8B is a top view of one embodiment of the bone screw of Figure 8 showing the incorporation of a channel groove vent;

Figure 9 is a side view of a device in accordance with one embodiment of the present invention in the form of yet another bone screw;

Figure 10 is a cross-sectional view showing one application of the device in accordance with the present invention, such as in the form of the bone screw of Figure 9 in connection with a pedicle attachment to a spinal vertebrae.

Figure 11 is an exploded perspective view of one of the bone screws shown in conjunction with the application of Figure 10;

Figure 12 is an exploded perspective view of another of the bone screws shown in the application of Figure 10;

Figure 13 is a cross-sectional view of an attachment mechanism useful in conjunction with the devices in accordance with the present invention;

Figure 14 is a cross-sectional view of a further embodiment of an attachment mechanism useful in conjunction with the devices in accordance with the present invention;

Figure 15 is an exploded perspective view of a delivery device shown in conjunction with an attachment mechanism of the type shown in Figure 14 together with a device in the form of a bone screw in accordance with the present invention;

Figure 15A is a cross-sectional view of the fully assembled delivery mechanism of Figure 15; and

Figure 16 is a cross-sectional view of a delivery device in accordance with the present invention together with an adapter useful in the delivery of medicants to a region of interest.

DETAILED DESCRIPTION OF PREFERRED EXEMPLARY EMBODIMENTS OF THE INVENTION

While the way in which the present invention addresses the various disadvantages of prior art devices will be described in greater detail hereinbelow, in general, the present invention provides a method and apparatus for the enhancement of delivery mechanisms useful in connection with fixation devices for bodily use, which enhancement is obtained by modification of the device to improve fixation without deleteriously effecting the performance of the device.

As previously briefly mentioned, in accordance with its various aspects, the devices of the present invention have various applications. It should be appreciated that the illustrations provided herein are for illustrative purposes only and are in no way intended to limit the scope of the invention as set forth in the appended claims. With this in mind, to aid in describing preferred embodiments of the present invention, reference will be made in this description, to devices in the form of a bone screw and devices in the form of delivery devices. In this context, the term "bone screw" is intended to refer to screws of all type which are presently known or hereafter devised by those skilled in the art for use in connection with the internal fixation of fractures of, for example, human or other animal bones. In this regard, cortical screws, cancellous screws, ASIF screws and machine screws are all contemplated as being within the scope of the screws which can be useful in connection with the present invention. It should be appreciated, however, that any type of fixation device such as pins, nails and the like, which are used internally and/or externally are included within the scope of the present invention. Similarly, the term "delivery device" is intended to be broadly construed to refer to any device

configured for insertion into a bone for purposes of delivering to a region within, or on the bone, a particular material. As will be described, such materials include, but are not limited to, medicants, bone growth stimulators and the like.

For purposes of illustration and to provide a point of reference for the following disclosure, referring now to Figure 1, a typical long bone 10, such as a bone in the arm or leg of a human, suitably includes end portions 12 and a shaft portion 14 spanning therebetween. The cortex 16, as is known, forms the solid and hard outer layer of bone 10. The endosteum 18 and the periosteum 20 portions, respectively, form the inner and outer lining of cortex 16. End portions 12 are suitably filled with cancellous bone 22, and shaft portion 14 is filled with bone marrow 24.

As is known, bones of the type illustrated in Figure 1 as bone 10 can become weakened due to, for example disease and/or injury. For example, in old age, bones may loose minerals and become porous. Such porous bones tend to be brittle and slower to heal. Various other diseases or conditions of the bone can also result, for example those which tend to result from insufficient supplies of vitamins or minerals or those resulting from stress or overactivity. In general, and as is used herein, a break in a bone is typically referred to as a fracture. With momentary reference to Figure 2, for example, a fracture 44 may result in bone 10 fracture which may require fixation to enable proper healing. While fracture 44 is shown as being complete, that is extending entirely through the cortex 16 on each side of shaft portion 14 of bone 10, other fractures extending through only a portion of the bone or occurring at any portion or multiple places along the bone such as at the end, are of the type with which the methods and apparatus of the present invention may be used.

As is known, internal fixation of fractures, typically following reduction, can be accomplished through a variety of techniques such as through the use of pins, screws, plates and screws and/or medullary nails. In general, current technologies fail to take into full consideration the condition of the bone which has been fractured. That is, particularly in diseased bone such as osteoporotic bones, the fixation of the bone, such as through the use of screws, is difficult in that the fixation is about a portion which has demonstrated weakness. Thus, fixation, particularly internal fixation of the bone should take into consideration the inherent weakness of the bone

which is to be repaired. In this regard, current techniques which involve use of screws to fix the bone, with or without plates, suffer from inherent difficulties in that the fixation is to an inherently weak bone or portion thereof. The present invention addresses this inherent difficulty by providing, as will be described in greater detail hereinbelow, a method and apparatus such that the strength of the fixation to the bone is enhanced through use of the devices and the methods set forth herein.

As previously noted, although a complete fracture is depicted in Figure 2, fracture 44 may extend only through a portion of bone 10. Alternatively, bone 10 may be fractured into several pieces. In general, the type and severity of the fracture determines in part the number and type of fixation devices required. For the sake of simplicity, in general, the insertion of a single bone screw 30 will be initially shown and described, such as, for example, in connection with Figures 3 and 4. It should be appreciated, however, that screw 30 suitably can be used in conjunction with any number of conventional or hereafter developed fixation devices such as pins, wires, plates, rods and the like to appropriately support and hold bone 10 (none of which are shown in Figures 3 and 4).

With reference now to Figure 3, in accordance with one aspect of the present invention, prior to insertion of screw 30, a bore 50 is suitably drilled in bone 10 using methods known in the art. Preferably, bore 50 has an associated bore axis 52 which, although illustrated in Figure 3 as being substantially orthogonal to the longitudinal axis of the bone, may be disposed at any desired angle with respect to the surface of the bone. For example, in complex fractures where multiple bone screws are used, as is known, it can be desirable to place screw 30 perpendicular to the fracture line rather than the surface of the bone.

Bore 50 suitably extends through cortex 16, matter 19 and opposing cortex 16. Matter 19 is suitably filled with cancellous bone 22 (Figure 1) in the ends of long bones and filled with bone marrow 24 (Figure 1) in the shaft of long bones. In certain applications, bore 50 may extend only partly into cortex 17 or not at all. For example, when bone screws are used in conjunction with a fixation plate, the screws used to secure the ends of the plate may be inserted through only one cortex to reduce stress at the ends of the plate.

With reference now to Figure 4, bone screw 30 is suitably inserted into bore 50. Although screw 30 may be directly inserted into bone 10, pre-drilling bone 10 with bore 50 preferably reduces the likelihood that bone 10 will splinter as screw 30 is inserted into bone 10. Additionally, bore 50 facilitates more accurate placement of screw 30 in bone 10. Suitable sizing of bore 50 can be determined from known techniques, which for ease of description, will not be herein detailed.

In accordance with one embodiment of the present invention, screw 30 preferably evidences the configuration of a standard cortex screw having a proximal (or top) end 32, a distal (or bottom) end 36 and a shaft 34 spanning therebetween. In accordance with the various exemplary embodiments of the present invention described herein, screw 30 is preferably formed in one piece from any number of strong materials, such as steel, titanium alloys, and the like. Additionally, bone-growth agents can be applied to screw 30 to promote bone growth around screw 30 thereby further securing screw 30 within bone 10.

Shaft 34 preferably evidences threads 37. Threads 37 suitably evidence a major diameter, (*i.e.*, two times the radius measured from the center line of screw 30 to the crest of a particular tooth) and a minor diameter, (*i.e.*, two times the radius measured from the center line to the bottom of a tooth) and a pitch. The major and minor diameters may be selected as appropriate for a particular application, as may be the pitch.

As shown, in this embodiment, screw 30 evidences threads 37 formed substantially along the entire length of shaft 34. It should be appreciated, however, that threads 37 may be formed along only a portion of shaft 34, or intermittently upon various portions of shaft 34, depending upon any particular application.

Distal end 36 suitably forms a tip which is preferably cone-shaped. In accordance with the illustrated embodiments, tip 36 evidences a closed end. It should be appreciated, however, as will be described in greater detail in connection with various other embodiments of the present invention, that tip 36, in certain applications, may be open. Although not shown, tip 36 may be provided with cutting flutes or otherwise be configured in a self-tapping manner.

As shown best in Figure 4, screw 30 preferably evidences an axial bore 31 which spans from head 32 in proximity to tip 36. Bore 31 may be formed in any suitable fashion. For

example, in accordance with various aspects of this embodiment of the present invention, bore 31 may be formed in the configuration of a cannulated bone screw, and as previously briefly noted, extend through the entire length of screw 30, or as shown, include a closed distal or bottom end.

In accordance with a preferred aspect of the present invention, top head 32 is suitably configured to exhibit an appropriate external profile and an appropriate internal profile. In this regard, in general, the external profile of head 32 is suitably configured for receipt of any suitable driving device. In the context of bone screw 30 illustrated in Figures 3 and 4, head 32 suitably exhibits a geometric configuration suitable for receipt of a handle or other suitable driving device useful for turning screw 30 into bore 50.

The internal profile of head 32 preferably includes a recess 38. Preferably, recess 38 is suitably configured to either aid in insertion of screw 30 into bore 50, enable receipt of a fluid delivery device, or both. As illustrated in Figure 4, in accordance with one aspect of this embodiment of the present embodiment, recess 38 evidences a tapped top which communicates with bore 31 as will be described hereinbelow. Such a tapped top is suitable for receipt of a syringe or other fluid delivery device. Head 32 may be suitably configured for any particular application. For example, as shown in the illustrated embodiment of Figure 4, head 32 can be provided with a beveled or curved lower surface in proximity between head portion and shaft portion 34 of bone screw 30. In this manner, stress and strain which can tend to concentrate at the interface between head portion 32 and shaft portion 34 can be minimized.

It should be appreciated that the external and internal profiles of head 32 may be adapted for any particular application. As will be described in greater detail hereinbelow, in accordance with various aspects of the present invention, the internal profile of head 32 is suitably configured to aid in the attachment of a fluid delivery device. In accordance with other aspects of the present invention, however, the internal profile of head 32 may be configured in any form which is suitable for receipt of such a fluid delivery device. Similarly, the external profile of head 32 may be configured in any fashion suitable to enable insertion of screw 32 into, for example, bore 50.

In accordance with a preferred aspect of this embodiment of the present invention, screw 30 is suitably provided with one or more radially extending slots, for example, the respective

||

illustrated slots 40 and 42. As will be described in greater detail hereinbelow, the number, location and configuration of slots 40, 42 may be varied for any particular application. In accordance with the illustrated embodiment, slot 40 is suitably located in proximity to the proximal portion of screw 30, and slot 42 is suitably located in proximity to the distal portion of screw 30. Slots 40, 42 preferably extend radially outwardly from bore 31, and as will be described hereinbelow, aid in the delivery of an injectable material into a desired region of interest during use of screw 30. As shown in Figure 4, in accordance with this embodiment, slot 40 is suitably positioned along the length of screw 30 such that when it is placed within bone 10, slot 40 is oriented with respect to the endosteum 18 of cortex 16. Further, in accordance with this embodiment of the present invention, slot 42, when screw 30 is positioned within bone 10, is suitably positioned in proximity to the periosteum 20 of the lower most portion of cortex 16, as such is shown best in Figure 4.

In accordance with various aspects of the present invention, slots 40, 42 are suitably positioned along shaft 34 of bone screw 30 so as to provide a suitable exit for material injected into bore 31 but in a manner which is calculated to minimize the effect of inclusion of slots 40, 42 on the structural integrity of screw 30. While any number and orientation of slots 40, 42 may be appropriate in a particular application, preferably, and in accordance with preferred aspects of the present invention, slots 40, 42 are placed in proximity to threads 37 so as to not impede the performance of threads 37. Stated another way, preferably slots 40 and 42 are placed above the grooves forming threads 37 so as to not impede or otherwise interfere substantially with the performance of the adjacent thread. For example, slots may be placed such that they fit within the pitch of the thread in an appropriate and suitable fashion. The present inventors have found that locating the slots in such fashion tends to minimize the effects of inclusion of slots 40, 42 on the integrity of screw 30. It should be appreciated, however, that in some applications the precise location of a particular configuration slot to be provided in the context of any screw 30, particularly where more than one slot is provided in any particular screw, the precise location may be such as to fall outside of the pitch of any particular thread. For example, slots may be provided along the shaft or non-threaded portion of screw 30.

Slots 40, 42 may also be aligned in any suitable fashion. In accordance with a preferred aspect of the present invention and as shown in the illustrated embodiment of Figure 4, slots 40 and 42 may be orthogonally aligned. For example, as shown in Figure 4, the central axis of slot 40 is orthogonal to the central axis of slot 42. It should be appreciated, however, that other alignments may be used. For example, slots 40 and 42 may be similarly aligned and extend radially outwardly from bore 50 in a substantially identical fashion. Alternatively, three slots (not shown) may be positioned to radially extend outward from the central bore at equidistant locations (*i.e.*, 120 degrees). Further, slots 40, 42 may be aligned in an angular orientation which is greater than or less than 90 degrees. That is, the slots may be angled upwardly or downwardly and offset from a typical radial orientation. In general, any number and orientation of slots as may be desirable for a particular application can be used in accordance with the present invention. Nevertheless, in accordance with a preferred embodiment, orthogonal orientation of the slots tends to enhance rigidity and strength of screw 30.

As used herein, the term "slot" refers to any radially extending aperture which extends from the outer most portion of screw 30 into and in communication with bore 31. Injectable material injected into bore (cannula) 31, is suitably delivered to desirable delivery sites by slots 40, 42, which preferably extend radially outward from cannula 38. In this manner, bone cement delivered through slots 40 and 42 harden to form respective cement masses 46 and 48 near cortex 16 to secure screw 30 to bone 10.

Slots 40 may suitably exhibit any geometric configuration for example, round or circular, star-shaped or other geometric configurations as may be appropriately used. In accordance with a preferred aspect of the present invention, and as shown in the illustrated embodiment of Figure 4, slots 40 and 42 exhibit a generally oblong or oval geometric configuration.

The transverse configuration of slots 40 and 42 may also be suitably selected for any particular application. In accordance with a preferred aspect of this embodiment of the present invention, slots 40, 42 exhibit a generally uniform cross-sectional configuration about their length, *i.e.*, the portion extending from bore 31 to the outer most portion of screw 30. It should be appreciated, however, that varying cross-sectional areas may, in appropriate cases, be utilized. Furthermore, the radial orientation of slots 40 and 42 may be selected as may be appropriate for a

13

particular application. In accordance with a preferred aspect of this embodiment of the present invention and as shown in the illustrated embodiment of Figure 4, slots 40 and 42 extend laterally in a substantially uniform fashion from bore 31 to the outermost portion of screw 30. It should be appreciated, however, that various angular orientations of the radially extending slots may be utilized. For example, slot 40 may suitably be configured to exhibit an angular orientation in a downward fashion or upward fashion. Slot 42 may also be suitably configured.

In accordance with various aspects of the present invention, the cross-sectional areas of slots 40 and 42 are preferably larger than that of cannula 31, thereby facilitating pressure control when material is injected through cannula 31. For example, in accordance with one exemplary embodiment of screw 30, the long diameters of slots 40 and 42 may be on the order of about 2.0 mm, and short diameters on the order of about 1.2 mm for a bone screw 30 wherein the diameter of cannula 31 is on the order of 1.3 mm.

In accordance with a preferred aspect of the present invention, screw 30 is suitably inserted into bore 50 of bone 10 in an appropriate manner, such as by attachment of any suitable insertion device (not shown) attached to head 32. Once screw 30 is thus suitably inserted into bone 10 in proximity to fracture 44, a suitable delivery device (not shown in Figure 4) is attached to head 32, such as in proximity thereto, and preferably in a substantially sealed manner to recess 38 to provide an inlet for an injectable fluid (e.g., bone cement) which is useful in enhancing the fixation of screw 30 to bone 10. In this manner, and in accordance with one aspect of the present invention, a syringe, cement gun or the like may be suitably attached to head 32, the lower most portion of the syringe communicating with recess 38. The delivery device (not shown) can suitably be filled with an appropriate cement. Any cement useful in connection with conventional fixation devices may be used. Preferably, low viscosity cements are used such as conventional polymethacrylate cements. However, other acrylic cements, resorbable materials and the like may be used as appropriate to aid in fixation of screw 30 to bone 10.

In accordance with one aspect of the present invention, a syringe filled with a suitable cement, is attached to screw 30 such that the cement can be injected into bore 31 of screw 32. As injected, an appreciable amount of cement will be caused to pass through bore 31 and through respective slots 40 and 42 thereby enabling formation of respective cement regions 46, 48 in

proximity to slots 40 and 42. As shown in the illustrated embodiment of Figure 4, regions 46 and 48 serve to enhance fixation of screw 30 to bone 10 by providing support of screw 30 in proximity to the outer most portions, *e.g.*, cortex portions of bone 10.

As will be described herein, various modifications can be made in the orientation of the slots to provide enhanced and/or alternative cement regions which aid in fixation of the devices of the present invention to the bone in regions of interest. In addition, in accordance with various alternative embodiments of the present invention, materials other than acrylic resins, (*e.g.*, bone cements) may be used and delivered to regions of interest.

It should be appreciated, particularly in the context of the embodiment of the present invention illustrated in Figure 4, that utilization of the device and methods of the present invention enable significant advantages over prior art systems. Particularly, in the case of osteoporotic bones, the provision of cement in proximity to fracture 44 tends to strengthen the fixation of screw 30 about a region of bone 10 which has in such cases demonstrated an inherent weakness. Stated another way, the provision of cement in proximity to both the inner and outer portions of bone 10 serve to fix screw 30 in a manner which has heretofore been unavailable through prior art devices and techniques.

Having now described the foregoing exemplary embodiment of the present invention, illustrated in Figure 4, various modifications in the design and arrangement can be made and are contemplated in connection with the present invention. As such, modifications as will be contemplated in light of the foregoing disclosure may be numerous, this application serves only to illustrate various applications and modifications. These modifications are provided for illustrative purposes only and are not intended in any way to limit the scope of the subject invention.

In this regard, and with reference now to Figures 5 and 5A, a further embodiment of a device in accordance with the present invention is shown. Specifically, a device in the form of a bone screw 130 is shown as evidencing a length L_1 . Length L_1 may be any appropriate dimension depending on the particular application for which bone screw 130 is desired. Screw 130, like screw 30 of Figures 3 and 4, suitably includes a head portion 132, a tip portion 136 and a shaft 134 spanning therebetween. Shaft 134 suitably includes a plurality of threads 137

15

spanning a length L_4 . As previously briefly noted, length L_4 may be equal to or less than length L_1 . Head 132 is suitably provided with a fluid receiving region 138 internally thereof. Head 32 suitably exhibits an internal or external profile appropriate for receipt of a conventional driving tool. An internal bore or cannula 131 extends about the length L_1 of screw 130. In contrast to screw 30, cannula 131 extends about the entire length of screw 130. In certain applications, to control the flow of the injectable material, a plug 141 may be inserted into the distal end of tip 136. Respective radially extending slots 140 and 142 are suitably provided at discrete points about shaft 134. Preferably, bore 140 is located at a distance of L_5 from top or head 132 of screw 130. Length L_5 may be suitably selected for appropriate positioning of bore 40 for any particular application. Similarly, bore 142 is suitably provided at a distance L_3 from head 132; again, the length of L_3 may be suitably selected for any particular application. In accordance with a preferred aspect of the present invention, the sum of lengths L_3 and L_5 exceeds the length L_1 of screw 131. However, in appropriate circumstances, the sum of lengths L_3 and L_5 may be equal to or less than the length L_1 of screw 131.

With reference now to Figure 5B, screw 132 may be suitably provided with appropriate markings 152 proximate head 132. With momentary reference to Figure 5B, the top of head portion 132 of screw 130 in accordance with one embodiment of the present invention may be provided with appropriate markings 152. Markings 152 advantageously are oriented such as to position screw 130 and to indicate alignment of one of the plurality of slots, most preferably the alignment of slot 140. Such alignment may be made at the time of insertion or thereafter; for example, screw 130 can be aligned even after insertion into bone 10 to aid in delivery of injectable material to a specific location within bone 10. Although not acceptable in some cases, alignment may also be effected even after injection of the cement, but preferably prior to curing.

Various other modifications may be made in the devices in accordance with the present invention. For example, with reference now to Figure 6, a bone screw 230 may be suitably provided. Screw 230 preferably comprises a top 232, a distal end 236 and a shaft 234 extending therebetween. Shaft 234 suitably exhibits a plurality of threads 237. At least one, and preferably a plurality of slots 240, 242 are suitably provided in screw 234, which slots suitably extend radially outwardly from a central cannula 231 to the outer most portion of screw 230. Screw 230

16

is thus similar to screws 30 and 130, however, in the context of the illustrated embodiment of Figure 6, slots 240 and 242 are axially aligned. Stated another way, and as is shown, slots 240 and 242 radially extend about a substantially aligned plane co-extensive with the axis of cannula 231.

As shown in Figure 6, screw 230 may be suitably configured for use in connection with a bone plate 239, preferably of conventional configuration. As is known, in connection with serious fractures it may be appropriate to internally fix bone 10 through use of plate 239 into which a plurality of screws (*e.g.*, screws 230) are received. In a fashion similar to use of screw 30, screw 230 may be suitably inserted into bone 10; however, in the case of this embodiment with use of plate 239, screw 230 is initially inserted through plate 239 as it is introduced, it passes through the plate and also into the upper most portion of bone 10. Once so inserted, injectable material may be inserted by communication of a delivery device (not shown in Figure 6) with receiving region 238 of top 232. As will be described in greater detail hereinbelow in connection with further exemplary embodiments of the present invention, cement may be first injected in proximity to bore 242, such as, for example, through use of an extending distribution device attached to the delivery device (both not shown). In this manner, cement may be initially delivered in proximity to bore 242; once so delivered, extension device may be removed, delivery device re-attached to screw 230 and cement delivered in proximity to top 232. In certain applications, multi-step cement introduction may be appropriate.

With reference now to Figure 7, multiple delivery sites may be provided in any particular device (*e.g.*, bone screw) useful in the context of the present invention. In accordance with this exemplary embodiment of the present invention, a bone screw 330 is provided which includes a top 332, a distal end 336 and a shaft 334 extending therebetween. Shaft 334 suitably exhibits threads 334 carried on the outermost portion thereof. A cannula 331 extending from top 332 about the entire length of screw 330, that is entirely to and through distal end 336 may be suitably provided. Screw 330 suitably also includes respective radially extending ports 340 and 342, which, as shown, are preferably orthogonally aligned relative to the axis of screw 330.

In use screw 330 enables for the formation of respective cement regions 346, 348 and 349. Specifically, in the context of use of screw 330 cement is injected, as described

17

hereinabove, into cannula 331 and cement is forced out of screw 330. Cement is injected into screw 330 via cannula 331 and caused to exit cannula 331 in proximity of tip 336 to form cement region 348. Similarly, cement is caused to exit in proximity to slot 342 to form cement region 349 and in proximity to slot 340 to form cement region 346. In this manner, as is shown,
5 significant support is engendered about screw 330 in proximity to distal end 336 on both the inner and outer sides of bone 10.

With reference now to Figure 8, a further embodiment of the present invention will now be described. In accordance with a preferred aspect of this embodiment of the present invention, a screw 430 is provided which is of the general configuration of a cancellous screw. As is
10 known, cancellous screws tend to have larger threads and are frequently used in metaphyseal areas. In general, they are threaded, as is shown, only about a portion of the length thereof. Specifically, and in accordance with preferred aspects of this embodiment of the present invention, screw 430 evidences a head 432, a tip 436 and a shaft 434 extending therebetween. As shown, shaft 434 is provided with a plurality of threads 437; however, threads 437 extend only about the bottom portion thereof thereby leaving a smooth shaft portion in the proximal portion of shaft 434. Preferably, as shown in Figure 8A, the threaded section of shaft 434 preferably evidences a larger thread than, for example, the threads of screws 330, 230, 130 and 30. In this fashion, screws 430 are suitable for use in soft cancellous bones in that the threads provide more purchase therein.

Screw 430 is provided with a central cannula 431 which extends from top 432 through the length of screw 430, but which cannula 431 does not extend through the entirety of screw 430. That is, tip 436 evidences a closed configuration. Respective slots 440 and 442 are provided in proximity to distal end 436. Head 432 is suitably configured to exhibit an external profile capable of adapting to an appropriate driving tool. Head 432 is further suitably
20 configured to exhibit an internal recess 438 for receipt of an appropriate fluid containing device.

Preferably, as shown best in Figure 8A, respective slots 440 and 442 are closely positioned relative to one another. Preferably, as previously noted, slots 440 and 442 are suitably provided in a manner which is calculated not to significantly impede the strength or performance of screw 430. Slots 440 and 442 of screw 430 are suitably arranged in any convenient fashion in

18

proximity to distal end 436. Preferably, and in accordance with a preferred aspect of this embodiment of the present invention, slots 440 and 442 are suitably provided as radially extending transverse paths from slot 431 to the outermost portion of screw 430. Preferably, as shown best in Figure 8A, slots 440 and 442 are oriented within the pitch of the thread.

5 In accordance with a preferred aspect of this embodiment of the present invention, screw 430 is provided with respective channel groove vents 441 and 443 which preferably extend about the length, or a portion thereof, of shaft 434. In accordance with a preferred aspect of this embodiment of the present invention, and with continued reference to Figures 8 and 8B, channel groove vents 441, 443 are suitably provided about a portion of screw 430 which extends
10 upwardly (*e.g.*, proximately) of slots 440 and 442. However, in accordance with various alternatives of this embodiment of the present invention, vent grooves 441 and 443 may be provided about the entire length thereof.

As will be appreciated by those skilled in the art, in certain applications it is desirous to provide a channel for evacuation of material which is displaced by introduction of cement into the bone. In accordance with conventional practices, which in various applications may be utilized in connection with the screws disclosed herein, venting is obtained by drilling a vent hole adjacent the bore (for example bore 50) which bore (*i.e.*, vent) provides a channel for exiting of materials which are displaced when cement is inserted into the bore, such as via bone screw 430. In general, as shown best in Figure 8B, vent grooves 441 and 443 are suitably provided by cutting from the major to minor groove of the thread pattern 437 of shaft 434. Provision of vent grooves 441 and 443, in the context of the present invention, enables material to be displaced in proximity to screw 430 and avoids the necessity of further drilling for vent purposes in proximity to the entry point of screw 430.

Although vent grooves 441 and 443 are shown as being generally in line with slots 440 and 442, alternative configurations may be utilized. For example, vents 441, 443 may be skewed relative to the angular orientation of slots 440 and 442, or such may be provided in various angular orientations relative to the other. For example, although as shown in Figure 8B the angle theta which separates the center most portion of groove 441 and groove 443 is on the order of

183 degrees. Angles theta of less than 180 degrees may be acceptable in appropriate applications.

With reference now to Figure 9, the heads of the various screws and other devices disclosed herein may be modified for appropriate applications. For example, in the context of spinal attachment devices, the heads of the screws useful in the context of the present invention may be modified for receipt of external or internal (but external to the bone) support structures. With continued reference to Figure 9, a screw 530 in accordance with this embodiment of the present invention preferably comprises a head 532, a tip 536 and a body 534 extending therebetween. Head 532 is preferably provided with an articulating top 533 which is suitably configured in the form of a ball. As will be described in connection with Figures 10, 11 and 12, articulating top 533 easily enables positioning of screw 530 in a vertebra and attachment to screw 530 of the various support mechanisms and devices which are used in spinal fixation structures.

Preferably, and as shown, screw 530 evidences a central bore 531 which extends only about a portion of screw 530. Respective slots 540 and 542 are suitably provided in proximity to tip 536, slots 540 and 542 extend radially from cannula 531 outwardly to the outermost portion of screw 530.

As is shown best in Figure 10, screws of the type shown in Figure 9, namely screws 530A and 530B are suitably configured for pedicle insertion to enable the formation of a support structure, in a conventional fashion, parallel to the spinal column. In this fashion, distal ends 536A, 536B of screws 530A and 530B are inserted into the respective centra of the vertebrae in a fashion similar to the insertion techniques described hereinabove. Other spinal applications, of course, may also be accomplished through use of the methods and apparatus disclosed herein.

As shown in Figures 10-12, in accordance with this aspect of the present invention, screws 530A and 530B may be used as anchors for internal fixation devices. In contrast to external fixation devices, internal fixation devices are installed without extending through the skin of the patient, and thus, typically require low profile attachment to bone.

After screws 530A and 530B are suitably seated within a bone mass, a syringe or other suitable injection device is attached to respective recesses 538A, 538B in respective heads 533A and 533B. In a manner as previously described herein, bone cement is suitably delivered through

respective cannulas 531A and 531B to secure screws 530A and 530B within the bone mass and create, for example, respective cement masses 560 and 562.

After the screws have been secured, appropriate fixation components may be attached to articulating heads 533A and 533B. For example, and with specific reference now to ^{Figure} ~~Figures~~ 11 and 12, respectively, sleeves ⁵⁶³ 562 and 564 may suitably couple a fixator rod 566 to screw 530A. A bottom nut 567 is suitably tightened about sleeves ⁵⁶³ 562, 564. Sleeves 562, 564 are caused to tighten over head portion 533A and fixator rod 566 is suitably disposed between sleeves ⁵⁶³ 562, 564 and is secured by a top nut 568.

In a similar fashion, and with reference now to Figure ¹² ~~N~~, a fixator rod 570 may be suitably coupled to screw 530B using collar arrangement ~~572~~ suitably comprising respective sleeves 574 and 576. Respective sockets formed in sleeves 574 and 576 suitably tighten over articulating head 533B and rod 570 is received in a receiving portion 577 of sleeve 574. Preferably, a retaining nut 575 is suitably adhered to the uppermost portions of sleeves 574 and 576, such as is shown in Figure 10, thereby enabling assembly of the fixation device to articulating head 533B of screw 530B. As shown in Figures 10 and 11, preferably, screw 530B is configured to provide for a second delivery port 577, which port can be used to facilitate the delivery of a material (e.g., adhesives) through screw 530B. One of the advantages which can be obtained through use of fixation devices of the type described herein is in alignment of the particular fixation components. That is, given an articulating head, *i.e.*, alignment can be obtained after insertion of screws 530A and 530B.

In certain applications it may be desirable to prefill the devices, *e.g.*, screws disclosed herein. For example, the screw, such as screw 530B may be filled with an injectable material, *e.g.*, adhesive, medicant or otherwise, prior to insertion into the bone.

As described briefly hereinabove, preferably the devices in accordance with various aspects of the present invention are used in conjunction with delivery devices to facilitate the delivery of injectable materials (*e.g.*, fluids) into a region of a bone. In this regard, the present inventors have found that in various applications it may be desirable to utilize an adaptor to facilitate the substantially fluid tight delivery of the injectable material into the various bone screws disclosed herein.

With reference now to Figure 13, in accordance with one embodiment of this aspect of the present invention, an adaptor 80 is provided which includes a first end 82, a second end 84 and a body 86 spanning therebetween. Preferably, in proximity to end 82, body 86 exhibits a threaded region 88. An internal bore 90 is suitably provided about the axis of adapter 80 and includes a first end 92 and a second end 94. Preferably, first end 92 includes a central cannula and second end 94 includes an enlarged recessed region suitable for receipt of a syringe tip. Adapter 80 may be utilized in conjunction with any of the screws or other devices disclosed herein. For example, adaptor 80 may be configured for use in connection with bone screw 30. In such case, recess 38 of head 32 will be suitably configured to receive threaded region 88. Adapter 80 may be utilized in conjunction with bone screw 30 either before and/or after insertion into bone 10. For example, in the event adapter 80 is affixed to screw 30 prior to insertion of screw 30 into bone 10, end 84 is suitably configured for receipt of an appropriate driving mechanism (*e.g.*, screwdriver, wrench or the like). Alternatively, once screw 30 is inserted into a bone region, adapter 80 may be applied to facilitate the substantially fluid tight delivery of cement or other fluids into the bone 10.

In lieu of utilizing adapter 80, in accordance with various aspects of the present invention, in order to provide a fluid tight seal, the syringe or other fluid delivery device used for delivery of the injectable fluid may be suitably provided with threads, such as in the form of threads 88, which threads can be used to engage corresponding threads contained in the top portion, for example top portion 32, of screw 30.

With reference now to Figure 14, adapter 80 may be suitably configured to exhibit a quick connect-disconnect portion in lieu of threads 88. In this regard, adapter 80A suitably includes a first end 82A, a second end 84A and a body 86A substantially spanning therebetween. Screw 80A suitably includes an internal bore 90A spanning the length thereof including a first portion 92A and a second portion 94A. In the context of this particular aspect of this embodiment of the present invention, end 82A is suitably provided with a key-like quick connect-disconnect protrusion 88A, which protrusion suitably corresponds with corresponding receiving portion located in the top, for example top 32, of the bone screws disclosed herein.

5 In this regard, and in connection with the exploded depiction shown in Figure 15, quick connect-disconnect end 88A of adapter 80A may be suitably configured for attachment to screw 30 such as in proximity top portion 32 thereof. A fluid delivery mechanism 95 suitably including an injectable fluid 96 for delivery into a bony region is provided for communication with adapter 80A in proximity to end 84A. Fluid delivery mechanism 95, for example in the form of a syringe, may be of any conventional type, such as conventional slip-tip syringes, large catheter tip syringes and/or tapered or sleeve syringes. Other delivery devices as are now known or hereafter devised by those skilled in the art may also be utilized. In the context of this embodiment of the present invention, syringe 94 is suitably configured to operate in a conventional matter and deliver injectable fluid 96 into a bone region (not shown) via delivery through adapter 80A and screw 30. As previously briefly mentioned above, in accordance with one aspect of the current invention, a delivery aid may be utilized in the delivery of fluid (*e.g.*, cement) to the distal most regions of screw 30. As shown in Figures 15 and 15A, a delivery aid in the form of an extender tip 98 may be suitably provided to communicate with adapter 80A and syringe 94 so as to provide an extended delivery path for injectable fluid 96 within screw 30.

Although not shown in connection with any of the various figures, in addition to or as an alternative to use of fluid delivery aid 98, capping pins may be utilized to deliver (*e.g.*, by pushing) cement or other injectable fluids through slots and/or holes located about the length of the devices in accordance with the invention described herein.

As previously briefly referred to hereinabove, the various devices in accordance with the present invention may be suitably utilized in connection with the delivery of medicants, bone growth stimulators and/or other fluids. Given the particular configuration as has now been described, those skilled in the art will likely recognize that use of the devices disclosed herein may offer significant advantages over present delivery devices. For example, in treatment of a manastisized region of a bone, a device, in the form of device 30 may be utilized to aid in the delivery, even on a repeated basis, of medicants or other fluids to the manastisized region. Alternatively, a device in accordance with the present invention, for example screw 30, may be implanted within a bone in proximity to the manastisized region and a introduction aid, such as tubing or the like, can be attached to the head thereof to facilitate external delivery of such

medicants to the region of interest. In certain applications utilizing the devices in accordance with the present invention for the delivery of fluids to a bone region of interest it may be desirable to use conventional capping pins or other devices to, in effect, block the cannula (e.g., inner bore) of the screws disclosed herein after introduction of the injectable fluid.

5 For example, with reference now to Figure 16 a device 600, preferably in the form of a nail, may be inserted into a bone 622 lying underneath the skin 624 of a patient. As shown, screw 600 is suitably configured for insertion into the bone such that its distal end comes in contact with a tumorous region 620. As will be explained, through use of the nail 600, medicants may be delivered to region 620 to aid in treatment thereof. Screw 600 preferably includes a head 10 602, a shaft 606 with a central cannula 608 spanning therealong. A slot 614 is provided in the distal end of shaft 606 which slot 614 suitably communicates with cannula 608. Head 602 is suitably configured for receipt of an attachment mechanism 604 which is suitably used to secure attachment of a delivery tube 616. As shown, delivery tube 616 suitably extends from adaptor 604 through the skin 624 to provide for an external insertion point 618. Adaptor 618 is suitably configured for receipt of a medicant delivery device. In the context of this embodiment of the present invention, nail 600 may be provided with suitable notches or protrusion 612 to aid in securing nail 600 to bone 622.

13 20 23 26 29 32 35 38 41 44 47 50 53 56 59 62 65 68 71 74 77 80 83 86 89 92 95 98 101 104 107 110 113 116 119 122 125 128 131 134 137 140 143 146 149 152 155 158 161 164 167 170 173 176 179 182 185 188 191 194 197 200 203 206 209 212 215 218 221 224 227 230 233 236 239 242 245 248 251 254 257 260 263 266 269 272 275 278 281 284 287 290 293 296 299 302 305 308 311 314 317 320 323 326 329 332 335 338 341 344 347 350 353 356 359 362 365 368 371 374 377 380 383 386 389 392 395 398 401 404 407 410 413 416 419 422 425 428 431 434 437 440 443 446 449 452 455 458 461 464 467 470 473 476 479 482 485 488 491 494 497 500 503 506 509 512 515 518 521 524 527 530 533 536 539 542 545 548 551 554 557 560 563 566 569 572 575 578 581 584 587 590 593 596 599 602 605 608 611 614 617 620 623 626 629 632 635 638 641 644 647 650 653 656 659 662 665 668 671 674 677 680 683 686 689 692 695 698 701 704 707 710 713 716 719 722 725 728 731 734 737 740 743 746 749 752 755 758 761 764 767 770 773 776 779 782 785 788 791 794 797 800 803 806 809 812 815 818 821 824 827 830 833 836 839 842 845 848 851 854 857 860 863 866 869 872 875 878 881 884 887 890 893 896 899 902 905 908 911 914 917 920 923 926 929 932 935 938 941 944 947 950 953 956 959 962 965 968 971 974 977 980 983 986 989 992 995 998 1001 1004 1007 1010 1013 1016 1019 1022 1025 1028 1031 1034 1037 1040 1043 1046 1049 1052 1055 1058 1061 1064 1067 1070 1073 1076 1079 1082 1085 1088 1091 1094 1097 1100 1103 1106 1109 1112 1115 1118 1121 1124 1127 1130 1133 1136 1139 1142 1145 1148 1151 1154 1157 1160 1163 1166 1169 1172 1175 1178 1181 1184 1187 1190 1193 1196 1199 1202 1205 1208 1211 1214 1217 1220 1223 1226 1229 1232 1235 1238 1241 1244 1247 1250 1253 1256 1259 1262 1265 1268 1271 1274 1277 1280 1283 1286 1289 1292 1295 1298 1301 1304 1307 1310 1313 1316 1319 1322 1325 1328 1331 1334 1337 1340 1343 1346 1349 1352 1355 1358 1361 1364 1367 1370 1373 1376 1379 1382 1385 1388 1391 1394 1397 1400 1403 1406 1409 1412 1415 1418 1421 1424 1427 1430 1433 1436 1439 1442 1445 1448 1451 1454 1457 1460 1463 1466 1469 1472 1475 1478 1481 1484 1487 1490 1493 1496 1499 1502 1505 1508 1511 1514 1517 1520 1523 1526 1529 1532 1535 1538 1541 1544 1547 1550 1553 1556 1559 1562 1565 1568 1571 1574 1577 1580 1583 1586 1589 1592 1595 1598 1601 1604 1607 1610 1613 1616 1619 1622 1625 1628 1631 1634 1637 1640 1643 1646 1649 1652 1655 1658 1661 1664 1667 1670 1673 1676 1679 1682 1685 1688 1691 1694 1697 1700 1703 1706 1709 1712 1715 1718 1721 1724 1727 1730 1733 1736 1739 1742 1745 1748 1751 1754 1757 1760 1763 1766 1769 1772 1775 1778 1781 1784 1787 1790 1793 1796 1799 1802 1805 1808 1811 1814 1817 1820 1823 1826 1829 1832 1835 1838 1841 1844 1847 1850 1853 1856 1859 1862 1865 1868 1871 1874 1877 1880 1883 1886 1889 1892 1895 1898 1901 1904 1907 1910 1913 1916 1919 1922 1925 1928 1931 1934 1937 1940 1943 1946 1949 1952 1955 1958 1961 1964 1967 1970 1973 1976 1979 1982 1985 1988 1991 1994 1997 2000 2003 2006 2009 2012 2015 2018 2021 2024 2027 2030 2033 2036 2039 2042 2045 2048 2051 2054 2057 2060 2063 2066 2069 2072 2075 2078 2081 2084 2087 2090 2093 2096 2099 2102 2105 2108 2111 2114 2117 2120 2123 2126 2129 2132 2135 2138 2141 2144 2147 2150 2153 2156 2159 2162 2165 2168 2171 2174 2177 2180 2183 2186 2189 2192 2195 2198 2201 2204 2207 2210 2213 2216 2219 2222 2225 2228 2231 2234 2237 2240 2243 2246 2249 2252 2255 2258 2261 2264 2267 2270 2273 2276 2279 2282 2285 2288 2291 2294 2297 2300 2303 2306 2309 2312 2315 2318 2321 2324 2327 2330 2333 2336 2339 2342 2345 2348 2351 2354 2357 2360 2363 2366 2369 2372 2375 2378 2381 2384 2387 2390 2393 2396 2399 2402 2405 2408 2411 2414 2417 2420 2423 2426 2429 2432 2435 2438 2441 2444 2447 2450 2453 2456 2459 2462 2465 2468 2471 2474 2477 2480 2483 2486 2489 2492 2495 2498 2501 2504 2507 2510 2513 2516 2519 2522 2525 2528 2531 2534 2537 2540 2543 2546 2549 2552 2555 2558 2561 2564 2567 2570 2573 2576 2579 2582 2585 2588 2591 2594 2597 2600 2603 2606 2609 2612 2615 2618 2621 2624 2627 2630 2633 2636 2639 2642 2645 2648 2651 2654 2657 2660 2663 2666 2669 2672 2675 2678 2681 2684 2687 2690 2693 2696 2699 2702 2705 2708 2711 2714 2717 2720 2723 2726 2729 2732 2735 2738 2741 2744 2747 2750 2753 2756 2759 2762 2765 2768 2771 2774 2777 2780 2783 2786 2789 2792 2795 2798 2801 2804 2807 2810 2813 2816 2819 2822 2825 2828 2831 2834 2837 2840 2843 2846 2849 2852 2855 2858 2861 2864 2867 2870 2873 2876 2879 2882 2885 2888 2891 2894 2897 2900 2903 2906 2909 2912 2915 2918 2921 2924 2927 2930 2933 2936 2939 2942 2945 2948 2951 2954 2957 2960 2963 2966 2969 2972 2975 2978 2981 2984 2987 2990 2993 2996 2999 3002 3005 3008 3011 3014 3017 3020 3023 3026 3029 3032 3035 3038 3041 3044 3047 3050 3053 3056 3059 3062 3065 3068 3071 3074 3077 3080 3083 3086 3089 3092 3095 3098 3101 3104 3107 3110 3113 3116 3119 3122 3125 3128 3131 3134 3137 3140 3143 3146 3149 3152 3155 3158 3161 3164 3167 3170 3173 3176 3179 3182 3185 3188 3191 3194 3197 3200 3203 3206 3209 3212 3215 3218 3221 3224 3227 3230 3233 3236 3239 3242 3245 3248 3251 3254 3257 3260 3263 3266 3269 3272 3275 3278 3281 3284 3287 3290 3293 3296 3299 3302 3305 3308 3311 3314 3317 3320 3323 3326 3329 3332 3335 3338 3341 3344 3347 3350 3353 3356 3359 3362 3365 3368 3371 3374 3377 3380 3383 3386 3389 3392 3395 3398 3401 3404 3407 3410 3413 3416 3419 3422 3425 3428 3431 3434 3437 3440 3443 3446 3449 3452 3455 3458 3461 3464 3467 3470 3473 3476 3479 3482 3485 3488 3491 3494 3497 3500 3503 3506 3509 3512 3515 3518 3521 3524 3527 3530 3533 3536 3539 3542 3545 3548 3551 3554 3557 3560 3563 3566 3569 3572 3575 3578 3581 3584 3587 3590 3593 3596 3599 3602 3605 3608 3611 3614 3617 3620 3623 3626 3629 3632 3635 3638 3641 3644 3647 3650 3653 3656 3659 3662 3665 3668 3671 3674 3677 3680 3683 3686 3689 3692 3695 3698 3701 3704 3707 3710 3713 3716 3719 3722 3725 3728 3731 3734 3737 3740 3743 3746 3749 3752 3755 3758 3761 3764 3767 3770 3773 3776 3779 3782 3785 3788 3791 3794 3797 3800 3803 3806 3809 3812 3815 3818 3821 3824 3827 3830 3833 3836 3839 3842 3845 3848 3851 3854 3857 3860 3863 3866 3869 3872 3875 3878 3881 3884 3887 3890 3893 3896 3899 3902 3905 3908 3911 3914 3917 3920 3923 3926 3929 3932 3935 3938 3941 3944 3947 3950 3953 3956 3959 3962 3965 3968 3971 3974 3977 3980 3983 3986 3989 3992 3995 3998 4001 4004 4007 4010 4013 4016 4019 4022 4025 4028 4031 4034 4037 4040 4043 4046 4049 4052 4055 4058 4061 4064 4067 4070 4073 4076 4079 4082 4085 4088 4091 4094 4097 4100 4103 4106 4109 4112 4115 4118 4121 4124 4127 4130 4133 4136 4139 4142 4145 4148 4151 4154 4157 4160 4163 4166 4169 4172 4175 4178 4181 4184 4187 4190 4193 4196 4199 4202 4205 4208 4211 4214 4217 4220 4223 4226 4229 4232 4235 4238 4241 4244 4247 4250 4253 4256 4259 4262 4265 4268 4271 4274 4277 4280 4283 4286 4289 4292 4295 4298 4301 4304 4307 4310 4313 4316 4319 4322 4325 4328 4331 4334 4337 4340 4343 4346 4349 4352 4355 4358 4361 4364 4367 4370 4373 4376 4379 4382 4385 4388 4391 4394 4397 4400 4403 4406 4409 4412 4415 4418 4421 4424 4427 4430 4433 4436 4439 4442 4445 4448 4451 4454 4457 4460 4463 4466 4469 4472 4475 4478 4481 4484 4487 4490 4493 4496 4499 4502 4505 4508 4511 4514 4517 4520 4523 4526 4529 4532 4535 4538 4541 4544 4547 4550 4553 4556 4559 4562 4565 4568 4571 4574 4577 4580 4583 4586 4589 4592 4595 4598 4601 4604 4607 4610 4613 4616 4619 4622 4625 4628 4631 4634 4637 4640 4643 4646 4649 4652 4655 4658 4661 4664 4667 4670 4673 4676 4679 4682 4685 4688 4691 4694 4697 4700 4703 4706 4709 4712 4715 4718 4721 4724 4727 4730 4733 4736 4739 4742 4745 4748 4751 4754 4757 4760 4763 4766 4769 4772 4775 4778 4781 4784 4787 4790 4793 4796 4799 4802 4805 4808 4811 4814 4817 4820 4823 4826 4829 4832 4835 4838 4841 4844 4847 4850 4853 4856 4859 4862 4865 4868 4871 4874 4877 4880 4883 4886 4889 4892 4895 4898 4901 4904 4907 4910 4913 4916 4919 4922 4925 4928 4931 4934 4937 4940 4943 4946 4949 4952 4955 4958 4961 4964 4967 4970 4973 4976 4979 4982 4985 4988 4991 4994 4997 5000 5003 5006 5009 5012 5015 5018 5021 5024 5027 5030 5033 5036 5039 5042 5045 5048 5051 5054 5057 5060 5063 5066 5069 5072 5075 5078 5081 5084 5087 5090 5093 5096 5099 5102 5105 5108 5111 5114 5117 5120 5123 5126 5129 5132 5135 5138 5141 5144 5147 5150 5153 5156 5159 5162 5165 5168 5171 5174 5177 5180 5183 5186 5189 5192 5195 5198 5201 5204 5207 5210 5213 5216 5219 5222 5225 5228 5231 5234 5237 5240 5243 5246 5249 5252 5255 5258 5261 5264 5267 5270 5273 5276 5279 5282 5285 5288 5291 5294 5297 5300 5303 5306 5309 5312 5315 5318 5321 5324 5327 5330 5333 5336 5339 5342 5345 5348 5351 5354 5357 5360 5363 5366 5369 5372 5375 5378 5381 5384 5387 5390 5393 5396 5399 5402 5405 5408 5411 5414 5417 5420 5423 5426 5429 5432 5435 5438 5441 5444 5447 5450 5453 5456 5459 5462 5465 5468 5471 5474 5477 5480 5483 5486 5489 5492 5495 5498 5501 5504 5507 5510 5513 5516 5519 5522 5525 5528 5531 5534 5537 5540 5543 5546 5549 5552 5555 5558 5561 5564 5567 5570 5573 5576 5579 5582 5585 5588 5591 5594 5597 5600 5603 5606 5609 5612 5615 5618 5621 5624 5627 5630 5633 5636 5639 5642 5645 5648 5651 5654 5657 5660 5663 5666 5669 5672 5675 5678 5681 5684 5687 5690 5693 5696 5699 5702 5705 5708 5711 5714 5717 5720 5723 5726 5729 5732 5735 5738 5741 5744 5747 5750 5753 5756 5759 5762 5765 5768 5771 5774 5777 5780 5783 5786 5789 5792 5795 5798 5801 5804 5807 5810 5813 5816 5819 5822 5825 5828 5831 5834 5837 5840 5843 5846 5849 5852 5855 5858 5861 5864 5867 5870 5873 5876 5879 5882 5885 5888 5891 5894 5897 5900 5903 5906 5909 5912 5915 5918 5921 5924 5927 5930 5933 5936 5939 5942 5945 5948 5951 5954 5957 5960 5963 5966 5969 5972 5975 5978 5981 5984 5987 5990 5993 5996 6000

Although the present invention has been described in conjunction with particular embodiments illustrated in the appended drawing figures, various modifications may be made without departing from the spirit and scope of the invention as set forth in the appended claims. For example, the design and arrangement of the elements may be modified for particular applications, additional applications may be developed and/or methods utilized in view of the disclosures provided herein.

24